10 /521673 DT01 Rec'd PCT/FTC 18 JAN 2005

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1-9. (Canceled).

10. (New) A device for accessing a vehicle control system via a wireless link, comprising:

a gateway unit mounted in a vehicle which is connected on one side to at least one control unit in the vehicle and includes a link to at least one wireless network on the other side, the gateway unit being adapted so that it is freely configurable via the wireless link.

- 11. (New) The device according to claim 10, wherein the gateway unit further includes at least one microcomputer, which is equipped with a software platform permitting an expansion of software during operation.
- 12. (New) The device according to claim 11, wherein the software platform is a Java Virtual Machine.
- 13. (New) The device according to claim 10, wherein the gateway unit further includes a non-volatile buffer memory and components which provide communication of the gateway unit with a vehicle control unit via at last one vehicle bus.
- 14. (New) The device according to claim 13, wherein the at least one vehicle bus is one of a CAN bus, a MOST bus, and a K line.
- 15. (New) The device according to claim 10, wherein the gateway unit is further connected to a wireless modern for connection to a wireless network.
- 16. (New) The device according to claim 15, wherein the connection is implemented one of (a) directly and (b) via a bus.

- 17. (New) The device according to claim 11, wherein software is loadable into the microcomputer of the gateway unit via the wireless network, at least one of: (a) error memories being readable by control units connected to the gateway unit, (b) status information of the motor vehicle being retrievable, (c) software being loadable into other control units, and (d) at least one actuator of the motor vehicle being controllable with the help of the software.
- 18. (New) The device according to claim 13, wherein the non-volatile buffer memory stores at least one of: (a) results of remote queries and (b) at least one of protocols and sequence controls for at least one of addressing and reprogramming other control units via the vehicle bus.
- 19. (New) The device according to claim 18, wherein the results of remote queries include at least one of error codes and status information.